



m/v "Scan Atlantic"

Company E-Mail
shipping@scanscot.de
Company Webpage
www.scanscot-shipping.com

Builders:

Peene Werft, Wolgast, Germany

Built:

1999

Home Port:

Douglas

Flag:

Isle of Man (British)

Commercial Managers:

Scanscot Shipping Services (Deutschland) GmbH
 Montanhof/Kattrepel 2, 20095 Hamburg, Germany
 Tel. +49 (0) 40 325 40 20, Fax. +49 (0) 40 325 40 262

Type:

- RoRo/LoLo - Mpp Carrier

Dimensions

- LOA: 126,84 m
- LPP: 118,55m
- Breath moulded: 20,00m
- Breath overall: 20,19m
- Air Draft: abt. 35,05m
(less actual draft)
- Max. Draft: 6,65 m

Generators

- 2 Volvo Penta 163 AA
428 KW / 1800 RPM
- Bowthruster: Schottel
630 hp / 550 kw

Grain / Bale Capacity

- Bale Space:
abt. 530.000 CBFT
- Grain Space:
abt. 340.000 CBFT

Reeferplugs

- 40 reefer plugs

Tonnage

- Abt. 7200 TDW on 6,65m
- 8831/2793 GT/NT
- Panama NRT: 7810
- Suez GRT/NRT:
9234,08 / 7690,19

Tank Capacity

- 687,77 tons HFO
- 87,66 tons MGO

Hatch Openings

- 1 Hatch 91 x 16,30 m
covered by 8 Pontoons
- Lower Holds:
Hold 1+2: 25,5 M x 16,30 M
covered by 8 pontoons

RoRo Capacity

- 520 LM RoRo - Deck
- Sterndoor opening:
10,00 M x 6,20 M
- Sternramp Capacity:
350 Mtons

Class

- Germanischer Lloyd
- Iceclass E3
- SOLAS II-2-Reg.54
- RoRo Ship strengthened for
Heavy Cargo
- Equipped for carriage of
containers.

Speed/Consumption

- Average Speed: 14,5 KN on
abt. 24 MT/IFO 180 RME -25-
with shaft generator connected
at max. 2 Bft
- 1,5 MT Go Idle, 3 MT working
crane

Hold Equipment

- Suitable for IMO Cargoes
- Cargo light fitted
in all cargo holds
- natural and mechanically
ventilated box shaped

Container Capacity

- Hold: 250 TEU
Resp. 119 FEU + 12 TEU
- On Deck: 373 TEU
Resp. 180 FEU + 15 TEU
- Total: 623 TEU
Resp. 299 FEU + 27 TEU

Main Engine

- 1 Diesel engine, four stroke
single acting with
supercharging
- MAN B+W 12 V 32/40- 5760 kW
2366,0 kVA; 440/220 V
- controllable pitch propeller

Holds/Hatches/Heights

- One hatch 90,53 x 16,3 m,
which can be completely
opened or each cover
seperately.
- Upper/lower holds are box -
shaped - steel floored -
TD flush steel pontoons.
- 1 RORO Deck - clear length
of 103 m, width 16,30 m,
clear height of 6,20 m,
- 2 lower hold of 25,35 length
width of 15,55, clear height 5,05
- Tweendeck can be removed
in which case clear height in
lower hold 12,20 m.

Cranes

- Equipped with 2 cranes
portside mounted,
each of 150mt lifting
capacity at 14 m outreach,
combinable up to 300 mts
• respectively 60 mt at 33 mtr
outreach